

Flat Goods Cutter



GS-15TX

Flat Goods Cutter for Knit Materials

Flat goods cutter from Gateway® Systems is ideal for non-woven or stretchy knit materials.



SPECIFICATIONS

Shipping dimensions



* Standard machine is equipped to use a single roll of goods. Optional roll holders are available for up to 3 rolls.

Max feed speed 21 m/min (@ 50Hz) Approximate cycle time per queen 6 cyc/min (measured with material web 1370 mm) Max material thickness 15 mm .039"-.078" (1-2 mm) Min. material thickness Max material width 90.5" (2300 mm) ± .12" (3 mm) Accuracy Max # of programs 1 program Voltage 3 phase x 400/230VAC 50 cycles Current (amps) Air pressure (psi) 90 psi (6 bar) Air consumption (cfm) 6 cfm (170 dm3/min (28,3 dm/cyc)) Section 1 - 3,120 lbs (1415 kg) Weight Section 2 - 298 lbs (135 kg)

GS-15TX

The GS-15TX is a compact, highly efficient flat goods cutter that is ideal for non-woven or stretchy knit materials. It utilizes dual scissor blades to create a cleaner, better cut.

- · Measures and cuts knit materials.
- · Dual scissor blades.
- Cleaner cuts than any single-blade system.
- No machine downtime due to loose fibers getting clogged.
- Angled feed system helps feed materials smoother.

Global Systems Group® (GSG) is a collection of the world's leading mattress machinery companies. These GSG machinery companies represent leadingedge technology in computerized quilting machines and panel cutters, automated and conventional sewing machines, material handling solutions, and mattress-packaging equipment.

quarrata

forniture

Section 1 - 130" x 90.5" x 78.75" (3,3 x

Section 2 - 47" x 78.75" x 11.8" (1,2 x 2,0

2,3 x 2,0 m)

x 0,3 m)

800-343-8138 • 417-237-6254 • GSGcompanies.com









