

Quilt Repair



POQ-30HJ/NP


Long-Arm Quilt and Skip Repair Machine

Quilt repair machine from Porter[®] International offers an easy-to-operate jump foot that helps the operator follow the most intricate patterns on the largest and thickest panels.

SPECIFICATIONS	POQ-30HJ/NP
Stitch type	single needle lockstitch
Max Speed-rpm	1250
Recommended speed-rpm	900
Needle type	135X17
Needle size	23
Needle height	3/4" (19 mm)
Presser foot height	1/2" (12.7 mm)
Clearance under arm	30" (76 cm)
Max. thickness capacity	4" (101 mm)
Motor type	servo needle positioner
Voltage	220/240VAC SINGLE PHASE (alternative voltages available)
Current (amps)	30 AMP(MAX)
Air pressure (psi)	80PSI
Air consumption (cfm)	6.00 SCFM @ 80PSI
Weight (gross)	490 lbs / 222 kg
Shipping Dimensions	45 X 65 X 37 / 114 X 165 X 94 cm

The POQ-30HJ/NP is a quilt and skip repair machine featuring a straight-stitch lockstitch and electronic needle positioner. It accepts material up to 4'' (101 mm) and maintains a presser foot height of $\frac{1}{2}''$ (12.7 mm).

- 30" (760 cm) clearance under the sewing machine arm allows repair anywhere on the mattress panel.
- Includes electronic needle positioning servo motor.
- Slim Presser foot design gives operator full vision in the sewing area.
- Will repair from thin panels and borders up to thick and dense quilt packages.



Global Systems Group[®] (GSG) is a collection of the world's leading mattress machinery companies. These GSG machinery companies represent leadingedge technology in computerized quilting machines and panel cutters, automated and conventional sewing machines, material handling solutions, and mattress-packaging equipment.

800-343-8138 • 417-237-6254 • GSGcompanies.com



131 Zapletal Way Carthage, MO 64836 USA

TEKNOMAC MERELLO

quarrata forniture

NAHTEC

ANDERSON GALKIN



٩

