



GLOBAL SYSTEMS GROUP
A DIVISION OF LEGGETT & PLATT

800-343-8138

417-237-6254

gsgcompanies.com

info@gsgcompanies.com

300-PT Panel Binder Machine

The 300-PT Panel Binder Machine offers a 300U Singer-style sewing head and a single-needle chainstitch with walking-foot technology. It features a tape edge head configuration and higher lift for thicker pillowtops. 300-PT includes an electronic needle positioner for operating convenience and this ergonomically designed sewing station has a sewing head that slants up to 5% toward the operator.

Features & Benefits

- 300U Singer style sewing head
- Single needle chain stitch with walking foot
- Tape edge head configuration
- Higher lift for thicker pillowtops
- Electronic needle positioner
- Ergonomically designed sewing station with sewing head that slants up to 5% towards operator
- Material: ½" – 6" (12.7 mm – 152 mm)
- Speed: 2500 rpm @ 5 spi
- Footprint: 48" × 20" (1.2 m × .5 m)
- Presser foot height: ½" (12.7 mm)
- Yield: 130+/- buckets/8-hour shift

Specifications

Stitch Type 3 needle chainstitch

Std Folder 5" (12.7 cm) wide V gusset but up to 8 1/2" (216 mm)

Max Speed-rpm 2000



Recommended Speed- 1800
rpm

Stitches Per Inch 5

Needle Type 62 x 59

Needle Size 23

Needle Height 11 mm

Presser Foot Height 8 mm

Aux Feed Device Integral puller

Motor Type Electronic needle positioner

Max. Thickness Capacity 6 mm/quilted pkg

Voltage 220 VAC

Current 5 amps

Air Pressure 80 psi

Air Consumption (cfm) .5 CFM

Weight (gross) 1099 lbs.

Shipping Dimensions 99" x 51" x 79"

Footprint 108" x 34" (2.7 m x .86 m)