



GLOBAL SYSTEMS GROUP
A DIVISION OF LEGGETT & PLATT

Gribe
INTERNATIONAL

800-343-8138

417-237-6254

gsgcompanies.com

info@gsgcompanies.com

GS-15TX flat-goods cutter

This flat-goods cutter creates a clean cut with dual scissors action. It's ideal for use with stretch knit ticks as well as conventional flat materials. Produce up to 6 queen-size panels per minute with a maximum thickness up to 15 mm.

Features & Benefits

- Measures and cuts knit materials
- Dual scissors blades
- Much cleaner cuts than any single-blade system
- No machine downtime due to loose fibers getting clogged
- Angled feed system helps feed materials smoother



Specifications

Max Feed Speed 21 m/min (@ 50Hz)

Approximate Cycle Time Per Queen 6 cyc/min (measured with material web 1370 mm)

Max Material Thickness 15 mm

Min Material Thickness .039"-.078" (1-2 mm)

Max Material Width 90.5" (2300 mm)

Accuracy $\pm .12"$ (3 mm)

Max # of Programs 1 program

Voltage 3-phase x 400/230VAC 50 cycles

Current (amps) 16A

Air Pressure 90 psi (6 bar)

Air Consumption 6 cfm (170 dm³/min (28,3 dm³/cyc))

Weight Section 1 - 3,120 lbs (1,415 kg)
Section 2 - 298 lbs (135 kg)

Shipping Dimensions Section 1 - 130" x 90.5" x 78.75" (3, 3x2, 3x2, 0 m)
Section 2 - 47" x 78.75" x 11.8" (1, 2x2, 0x0, 3 m)