



**GLOBAL SYSTEMS GROUP**  
A DIVISION OF LEGGETT & PLATT

800-343-8138

417-237-6254

[gsgcompanies.com](http://gsgcompanies.com)

[info@gsgcompanies.com](mailto:info@gsgcompanies.com)

# POQ-30HJ/NP

The POQ-30HJ/NP is a quilt and skip repair machine featuring a straight-stitch lockstitch and electronic needle positioner. It accepts material up to 4" (101mm), and maintains a presser foot height of ½" (12.7mm). POQ-30HJ/NP operates at a speed of 1500rpm and has an arm length of 30" (760mm).



## Features & Benefits

- Quilt & Skip Repair Machine
- Straight stitch lockstitch
- Electronic needle positioner
- Arm length 30" (760 mm)
- Material: Up to 4" (101 mm)
- Speed: 1500 rpm
- Footprint: 60" x 30" (1.5 m x .76 m)
- Needle height: ¾" (19 mm)
- Presser foot height: ½" (12.7 mm)

## Specifications

**Stitch Type** Single needle lockstitch

**Max Speed-rpm** 1250

**Recommended Speed-** 900  
**rpm**

**Needle Type** 135 x 17

**Needle Size** 23

**Needle Height** ¾" (19 mm)

**Presser Foot Height** ½" (12.7 mm)

**Clearance Under Arm** 30" (76 cm)

**Max. Thickness Capacity** 4" (101 mm)

**Motor Type** servo needle positioner

**Voltage** 220/240 VAC SINGLE PHASE (alternative voltages available)

**Current** 30 AMP (MAX)

**Air Pressure** 80 PSI

**Air Consumption (cfm)** 6.00 SCFM @ 80PSI

**Weight (gross)** 490 lbs. / 222 kg

**Shipping Dimensions** 45 x 65 x 37 / 114 x 165 x 94 cm