



GLOBAL SYSTEMS GROUP
A DIVISION OF LEGGETT & PLATT

800-343-8138

417-237-6254

gsgcompanies.com

info@gsgcompanies.com

SSB-500 Single-Sided Bed Binder System

With Porter International's SSB-500 Single-Sided Bed Binder System, non-skid panels are flanged and taped to the border in one easy step. The SSB-500 prepares the non-quilted side of the no-flip bedding and eliminates pre-flanging on the non-skid panel. The high-lift walking foot sewing head accepts either border rolls or pre-closed borders. The single needle chain stitch machine handles material from ½ to 4 inches wide.



Specifications

Max Sewing Speed 3600 RPM

Recommended Sewing Speed 3000 RPM

Max Panel Thickness 4" (101 mm)

Min Panel Thickness 1/2" (12.7 mm)

SPI 5

Yield 160+ / foundations / 8 hour shift

Presser Foot Height 5/8" (15.875 mm)

Needle Type B27

Needle Size 23

Voltage 220 (alternative voltages available)

Current 5 amps

Air Pressure 80 psi

Air Consumption (cfm) 2-Jan

Weight 830 lbs. / 376 kg

Shipping Dimensions 73 x 58 x 65" / 185 x 147 x 165 cm



